

# GISUN power

*Supplied by*

 **JOG**  
International Ltd.



## 370-380W Solar Panel

## Electrical Characteristics

Module Type	M6-60-370	M6-60-375	M6-60-380
	STC	STC	STC
Maximum Power at STC (Pmp)	370	375	380
Open Circuit Voltage (Voc)	41.6	41.8	42.0
Short Circuit Current (Isc)	11.34	11.41	11.48
Maximum Power Voltage (Vmp)	34.6	34.8	35.0
Maximum Power Current (Imp)	10.70	10.78	10.86
Module Efficiency at STC( $\eta$ m)	20.3	20.6	20.9
Power Tolerance	(0, +4.99)		
Maximum System Voltage	1000 VDC		
Maximum Series Fuse Rating	20A		

STC: Irradiance 1000 W/m<sup>2</sup> module temperature 25°C AM=1.5;

## Temperature Characteristics



Pmax Temperature Coefficient	-0.36 %/°C
Voc Temperature Coefficient	-0.28 %/°C
Isc Temperature Coefficient	+0.05 %/°C
Operating Temperature	-40~+85 °C
Nominal Operating Cell Temperature (NOCT)	45±2°C
Fire Rating	Class C

## Mechanical Specifications


External Dimension	1755 x 1038 x 30 mm
Weight	19.5kg
Solar Cells	PERC Mono 166x83mm (120pcs)
Front Glass	3.2 mm AR coating tempered glass, low iron
Frame	Anodized aluminium alloy
Junction Box	IP68,3 diodes
Output Cables	4.0 mm <sup>2</sup> ,Portrait:900mm or Customized Length
Connector	Genuine MC4 Connector /Compatible MC4 Connector
Mechanical Load	Front side 5400 Pa/ Rear side 2400 Pa

## Packing Configuration

	1755 x 1038 x 30 mm
Container	40'HQ
Pieces per Pallet	38+38+4
Pallets per Container	13
Pieces per Container	1040




## I-V Curve



## Product Certificates



## Warranty



Guarantee on product material and workmanship



Linear power output warranty